


Personal Protective Equipment 				WHMIS Pictograms 		GHS Pictograms 	DOT Pictograms
Chemical Splash Goggles	Safety Glasses	Protective Gloves	Face shield	Corrosive Material	D2B Toxic	Causes severe skin burns and eye damage	Corrosive

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

Product Name: 2166-BN
Product Code: 2166-BN
MSDS Manufacturer Number: 2166-BN
Product Use/Restriction: Soldering flux
Manufacturer Name: Kester
Address: 800 W. Thorndale Avenue
Itasca, IL 60143
General Phone Number: (630)-616-4000
Customer Service Phone Number: (800)-2KESTER (253-7837)
CHEMTREC: CHEMTREC 24-Hour Emergency Telephone Number: (800)424-9300
CHEMTREC 24-Hour Emergency Telephone Number: ((Outside of the U.S. and Canada):): (703)527-3887
Website: mds@kester.com
MSDS Creation Date: August 15, 2008
MSDS Revision Date: September 17, 2009



HMIS	
Health Hazard	3
Fire Hazard	1
Reactivity	1
Personal Protection	X

* Chronic Health Effects

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Ingredient Percent	EC Num.
Proprietary ingredient(s)	Proprietary	30 - 60 by weight	
2-Butoxyethanol	111-76-2	1 - 5 by weight	
Non Hazardous	N/A	30 - 60 by weight	

SECTION 3 - HAZARDS IDENTIFICATION

Emergency Overview: WARNING! Severe Irritant. Flux fumes during soldering may cause irritation and damage of mucous membranes and respiratory system.
Route of Exposure: Eyes. Skin. Inhalation. Ingestion.
Acute Health Effects: Corrosive. Causes burns.
Eye: Smoke during soldering can cause eye irritation.
Skin: Prolonged exposure can cause severe irritation.
Inhalation: Inhalation of vapors, fumes or mists of the product causes severe respiratory system irritation.
Ingestion: Ingestion of the product may produce gastrointestinal irritation and disturbances.
Chronic Health Effects: Prolonged skin contact causes burns. Repeated or prolonged inhalation may cause toxic effects.
Signs/Symptoms: Depending on solution concentration, material may be corrosive to skin, mucous membranes and eyes. Vapors may cause respiratory irritation.
Target Organs: Eyes. Skin. Respiratory system. Digestive system.
Aggravation of Pre-Existing Conditions: May aggravate pre-existing respiratory disorders, allergy, eczema, or skin conditions.

SECTION 4 - FIRST AID MEASURES

Eye Contact: Immediately flush eyes with plenty of water for 15 to 20 minutes. Get medical attention, if irritation or symptoms of overexposure persists.
Skin Contact: Immediately wash skin with soap and plenty of water.

Inhalation:	Get medical attention if irritation develops or persists.
Ingestion:	If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.
Ingestion:	If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

SECTION 5 - FIRE FIGHTING MEASURES

Flash Point:	Not applicable.
Lower Flammable/Explosive Limit:	Not applicable.
Upper Flammable/Explosive Limit:	Not applicable.
Extinguishing Media:	Use alcohol resistant foam, carbon dioxide, dry chemical, or water fog or spray when fighting fires involving this material.
Unsuitable Media:	Do not use a solid water stream as it may scatter and spread fire.
Protective Equipment:	As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) and full protective gear.
Hazardous Combustion Byproducts:	Oxides of carbon, oxides of nitrogen, aliphatic aldehydes, and other organic substances may be formed during combustion..
NFPA Ratings:	
NFPA Health:	3
NFPA Flammability:	1
NFPA Reactivity:	1
NFPA Other:	

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personnel Precautions:	Evacuate area and keep unnecessary and unprotected personnel from entering the spill area. Avoid breathing vapor, aerosol or mist. Avoid contact with skin, eyes and clothing.
Environmental Precautions:	Avoid runoff into storm sewers, ditches, and waterways.
Methods for containment:	Contain spills with an inert absorbent material such as soil, sand or oil dry.
Methods for cleanup:	Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Provide ventilation. Clean up spills immediately observing precautions in the protective equipment section.

SECTION 7 - HANDLING and STORAGE

Handling:	Use with adequate ventilation. Avoid breathing vapor and fumes. Use only in accordance with directions.
Storage:	Store in a cool, dry, well ventilated area away from sources of heat and incompatible materials. Keep container tightly closed when not in use.
Hygiene Practices:	Wash thoroughly after handling. Avoid inhaling vapors, mists, or fumes.

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

Engineering Controls:	Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.
Eye/Face Protection:	Tightly fitting safety goggles. Wear a face shield also when splash hazard exist.
Hand Protection Description:	Wear appropriate protective gloves. Consult glove manufacturer's data for permeability data. Nitrile rubber or natural rubber gloves are recommended.
Respiratory Protection:	A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.
Other Protective:	Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

EXPOSURE GUIDELINES

<u>2-Butoxyethanol</u> :	
Guideline ACGIH:	TLV-TWA: 20 ppm
Guideline OSHA:	Skin: yes

SECTION 9 - PHYSICAL and CHEMICAL PROPERTIES

Physical State Appearance:	Liquid.
Color:	amber
Odor:	Odorless
Boiling Point:	100 °C (212 °F)

Melting Point:	0 °C (32 °F)
Density:	1.144 g/cm ³ @ 20°C (68°F)
Vapor Pressure:	19 mm Hg @ 20°C (68°F)
pH:	3.1 @ 20°C (68°F)
Flash Point:	Not applicable.

SECTION 10 - STABILITY and REACTIVITY

Chemical Stability:	Stable under normal temperatures and pressures.
Hazardous Polymerization:	Not reported.
Conditions to Avoid:	Keep away from heat, ignition sources and incompatible materials.
Incompatible Materials:	Oxidizing agents. Strong acids and alkalis.
Special Decomposition Products:	Carbon monoxide and carbon dioxide Aldehydes

SECTION 11 - TOXICOLOGICAL INFORMATION

2-Butoxyethanol :

RTECS Number:	KJ8575000
Eye:	Eye - Rabbit Standard Draize test: 100 mg/24H (RTECS)
Skin:	Administration onto the skin - Rabbit Open irritation test: 500 mg Administration onto the skin - Rabbit LD50: 220 mg/kg [Details of toxic effects not reported other than lethal dose value.] Administration onto the skin - Guinea pig LD50: 230 uL/kg [Details of toxic effects not reported other than lethal dose value.] (RTECS)
Inhalation:	Inhalation. - Rat LC50: 450 ppm/4H [Behavioral - ataxia Nutritional and Gross Metabolic - weight loss or decreased weight gain] Inhalation. - Mouse LC50: 700 ppm/7H [Behavioral - analgesia Lungs, Thorax, or Respiration - dyspnea Kidney/Ureter/Bladder - hematuria] Inhalation. - Mouse LC50: 3380 mg/m3/7H [Liver - other changes Kidney/Ureter/Bladder - other changes Blood - other hemolysis with or without anemia] Inhalation. - Rat LC50: 2900 mg/m3/7H [Liver - other changes Kidney/Ureter/Bladder - other changes Blood - other hemolysis with or without anemia] (RTECS)
Ingestion:	Oral - Mouse LD50: 1230 mg/kg [Behavioral - altered sleep time (including change in righting reflex) Behavioral - somnolence (general depressed activity) Skin and Appendages - hair] Oral - Mouse LD50: 1167 mg/kg [Liver - other changes Kidney/Ureter/Bladder - other changes Blood - other hemolysis with or without anemia] Oral - Rat LD50: 917 mg/kg [Liver - other changes Kidney/Ureter/Bladder - other changes Blood - other hemolysis with or without anemia] Oral - Rat LD50: 250 mg/kg [Details of toxic effects not reported other than lethal dose value.] (RTECS)

Non Hazardous :

RTECS Number:	ZC0110000
Ingestion:	Oral - Rat LD50 : >90 mL/kg [Details of toxic effects not reported other than lethal dose value.] (RTECS)

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity:	No ecotoxicity data was found for the product.
Environmental Fate:	No environmental information found for this product.

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Disposal:	Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local guidelines.
-----------------	---

SECTION 14 - TRANSPORT INFORMATION

DOT Shipping Name:	Corrosive liquid, acidic, organic, n.o.s.(Glycolic acid)
DOT UN Number:	UN3265
DOT Hazard Class:	8
DOT Packing Group:	II
IATA Shipping Name:	Corrosive liquid, acidic, organic, n.o.s.(Glycolic acid)
IATA UN Number:	UN3265
IATA Hazard Class:	8
IATA Packing Group:	II
IMDG UN Number :	UN3265
IMDG Shipping Name :	Corrosive liquid, acidic, organic, n.o.s.(Glycolic acid)
IMDG Hazard Class :	8
IMDG Packing Group :	II
RID UN Number :	UN3265
RID Shipping Name :	Corrosive liquid, acidic, organic, n.o.s.(Glycolic acid)

SECTION 15 - REGULATORY INFORMATION

Canada Reg. Status: This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all of the information required by the Controlled Products Regulations.

Canada WHMIS: Controlled - Class : D2B Toxic

2-Butoxyethanol :

TSCA Inventory Status: Listed

Canada DSL: Listed

Non Hazardous :

TSCA Inventory Status: Listed

Canada DSL: Listed

WHMIS Pictograms



SECTION 16 - ADDITIONAL INFORMATION

General Use: Soldering flux

HMIS Health Hazard: 3

HMIS Fire Hazard: 1

HMIS Reactivity: 1

HMIS Personal Protection: X

MSDS Creation Date: August 15, 2008

MSDS Revision Date: September 17, 2009

Disclaimer: The information contained herein is based on data considered accurate and is offered solely for information, consideration and investigation. Kester extends no warranties, makes no representations and assumes no responsibility as to the accuracy, completeness or suitability of this data for any purchaser's use. The data on this Material Safety Data Sheet relates only to this product and does not relate to use with any other material or in any process. All chemical products should be used only by, or under the direction of, technically qualified personnel who are aware of the hazards involved and the necessity for reasonable care in handling. Hazard communication regulations require that employees must be trained on how to use a Material Safety Data Sheet as a source for hazard information.

Copyright© 1996-2008 [Actio Software Corporation](#). All Rights Reserved.